



API DOCUMENT (GENERAL)

Version 5.1

ABSTRACT

This document contains different API details for the merchants that needs to connect to eCourier platform.

Table of Contents

Version History	3
1.0 API Authentication Parameters	4
2.0 APIs and Details	4
2.1 Place Order	4
2.1.1 Input Parameters	4
2.1.2 Request Format	5
2.1.3 Response Format	6
2.2 Parcel Tracking	7
2.2.1 Input Parameters	7
2.2.2 Request Format	7
2.2.3 Response Format	7
2.3 Packages	8
2.3.1 Request Format	9
2.3.2 Response Format	9
2.4 Cancel Order	9
2.4.1 Input Parameters	9
2.4.2 Request Format	9
2.4.3 Response Format	10
2.5 Fraud Alert Check	10
2.5.1 Input Parameters	10
2.5.2 Request Format	10
2.5.3 Response Format	10
2.6 City List	11
2.6.1 Request Format	11
2.6.2 Response Format	12
2.7 Thana List	12
2.7.1 Input Parameters	12
2.7.2 Request Format	12
2.7.3 Response Format	13
2.8 Area List by Post Code	14
2.8.1 Input Parameters	14
2.8.2 Request Format	14
2.8.3 Response Format	14
2.9 Post Code List	15
2.9.1 Input Parameters	15
2.9.2 Request Format	15
2.9.3 Response Format	15
2.10 Branch List	16

2.10.1 Request Format	16
2.10.2 Response Format	16
2.11 Booster SMS Service	16
2.11.1 Input Parameters	17
2.11.2 Request Format	17
2.11.3 Response Format	17
2.12 Booster Service Top-up	18
2.12.1 Input Parameters	18
2.12.2 Request Format	18
2.12.3 Response Format	18
2.13 Booster Top-up Status Check	19
2.13.1 Input Parameters	19
2.13.2 Request Format	19
2.13.3 Response Format	19
2.14 OTP SMS	20
2.14.1 Input Parameters	20
2.14.2 Request Format	20
2.14.3 Response Format	20
2.15 Child Parcel Tracking	21
2.15.1 Input Parameters	21
2.15.2 Request Format	22
2.15.3 Response Format	22
2.16 Label Print	23
2.16.1 Input Parameters	23
2.16.2 Request Format	23
2.16.3 Response Format	23
2.17 Child parcel cancel	23
2.17.1 Input Parameters	23
2.17.2 Request Format	23
2.17.3 Response Format	23
2.18 Payment Status	23
2.18.1 Input Parameters	23
2.18.2 Request Format	23
2.18.3 Response Format	23
3.0 Response Code Definition	26
4.0 Sandbox Base URL	26
5.0 Live Base URL	26

Version History

Version	Changes in this version	Release Date	Author
5.1	2 New API added. Child Order Cancel and Payment Status	16-Aug-2021	Debashis Nag
5.0	Introduced to additional parameter in Place Order API	11-Aug-2021	Debashis Nag

1.0 API Authentication Parameters

Name	Type	MOC	Description	VALUE
API-KEY	string	Mandatory	Your api key	*****
API-SECRET	string	Mandatory	Your api secret	*****
USER-ID	string	Mandatory	Login ID	*****
Content-type	string	Mandatory	Request content type	application/json

* Authentication parameters are needed to be added header part of each request.

2.0 APIs and Details

2.1 Place Order

- ✧ Purpose: To place order
- ✧ Method: POST
- ✧ Path: /order-place

2.1.1 Input Parameters

Name	TYPE	MOC	Description	Sample value
recipient_name	String	Mandatory	Parcel receiver's name. Not more than 250 Characters	Lal
recipient_mobile	String	Mandatory	Parcel receiver's mobile number. Exactly 11 digit long	01XXXXXXXXXX
recipient_city	String	Mandatory	Parcel receiver's City. Not more than 40 characters	Dhaka
recipient_thana	String	Mandatory	Parcel receiver's Thana. Not more than 40 characters	Dhaka
recipient_area	String	Mandatory	Parcel receiver's area. Not more than 40 character	Dhanmondi 27
recipient_address	String	Mandatory	Parcel receiver's address detail. Not more than 40 characters	House#34,Road#4,Block#4 Or Gudaraghat, North Badda Or Village:Rosulpur, Post:Post, Thana:Thana, Dist: District

package_code	String	Mandatory	Your package code	#1234
product_price	Integer	Mandatory	Your Product Price	1200
payment_method	String	Mandatory	Your Payment Method	Cash On Delivery – COD, Point of Sale – POS, Mobile Payment – MPAY, Card Payment – CCRD
recipient_zip	String	Mandatory	Receiver’s ZIP Code	1212 Default null
parcel_type	String	Optional	Your parcel type	For box -> BOX For Documents -> DOC Default BOX
requested_delivery_time	String	Optional	Request Delivery time	Selected day (YYYY-MM-DD) Default Next day
product_id	String	Optional	Your product ID. Not more than 20 characters	AR123321 Default null
pick_address	String	Optional	Your alternative pick addresses. Not more than 255 characters	Any valid address. Default null
pick_hub	Integer	Optional	The hub id from where parcel is picked. Integer	Any integer
comments	String	Optional	Instructions for delivery. not than 255 characters	Default null
number_of_item	Integer	Optional	Total product	Default 1
actual_product_price	Integer	Optional	Actual product price	Default 0
special_instruction	String	Optional	About product	Default null
pgwid	String	Optional	Payment gateway ID. eCourier will share with merchant	Default null
pgwtxn_id	String	Optional	Payment gateway transaction ID	Default null

2.1.2 Request Format

Header	Body
Headers [API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json]	Body { "recipient_name": "Debashis", "recipient_mobile": "01834795469", "recipient_city": "Dhaka", "recipient_area": "Badda", "recipient_thana": "Badda", "recipient_address": "Full Address", "package_code": "#2431", "product_price": 1500, "payment_method": "COD", "recipient_landmark": "DBBL ATM", "parcel_type": "BOX", "requested_delivery_time": "2019-07-05", "delivery_hour": "any", "recipient_zip": "1212", "pick_hub": "3" "product_id": "DAFS", "pick_address": "Gudaraghat new mobile", "comments": "Please handle carefully", "number_of_item": "3", "actual_product_price": 1200, "pgwid": EC90817, "pgwtxn_id": "asdadsad" }

2.1.3 Response Format

Status	Response
200 Request accepted	<pre>{ "errors": [], "response_code": 200, "message": "Order Submitted", "ID": "ECR1030102170392" }</pre>
401 Unauthorized Access	User does not have permission or authentication failed due to wrong credentials <pre>{ "errors": ["Unauthorized Access"], "response_code": 401 }</pre>
400 Bad Request	Required parameter is missing or not set <pre>{ "errors": ["Invalid Request", "recipient_name Parameter either missing or not set correctly. "], "response_code": 400 }</pre>
400 Bad Request	Package selection is incorrect <pre>{ "errors": ["Invalid Package", "The Package code does not exist or assigned to you"], "response_code": 400 }</pre>
400 Bad Request	Product price and payment mismatch <pre>{</pre>

	<pre> "errors": ["Invalid Request", "Product price 0 not allow in BOD and COD payment method"], "response_code": 400 } </pre>
400 Bad Request	<pre> Duplicate product id and mobile { "errors": ["Invalid Request", "Duplicate product id and mobile supplied"], "response_code": 400 } </pre>
500 Internal Server Error	<pre> Server or System error { "errors": ["Unable to insert orders"], "response_code": 500 } </pre>

2.2 Parcel Tracking

- ✧ Purpose: To track parcel
- ✧ Method: POST
- ✧ Path: /track

2.2.1 Input Parameters

Name	TYPE	MOC	Description	Sample value
Product_id	String	Conditional	Your product id	ASD123
ecr	String	Conditional	Your eCourier ID	ECR1012312321312

2.2.2 Request Format

Header	Body
<pre> Headers [API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json] </pre>	<pre> Body { " product_id": "1234", " ecr": "ECR0032042424" } Or { " product_id": "1234" } Or { "ecr": "ECR0032042424" } </pre>

2.2.3 Response Format

Status	Response
--------	----------

200 Request accepted	<pre>When Order doesn't exist { "response_code": 200, "message": "Success", "query_data": "No Data Found" }</pre>
200 Request accepted	<pre>When Data Found { "response_code":200,"message":"Success", "query_data": [{"status": [["Delivered","","2017-01-20 12:04:55"], ["On the way to Delivery","Status has been changed", "2017-01-20 12:03:39"], ["In Destination Branch","Status has been changed", "2017-01-20 12:03:34"], ["In Transit","Status has been changed", "2017-01-20 12:03:25"], ["In Source Branch","Status has been changed", "2017-01-20 12:03:20"], ["Picked Up","Status has been changed", "2017-01-20 12:01:37"], ["Initiated","An order has been made by ecommerce", "2017-01-20 12:00:09"]] }, "REFID":"ECR1022001175478","company":"MyTOTOcompany", "product_id":"","r_name":"Mannan","r_mobile":"01848308508", "r_address":"House:d,Block:d,Road:d,Area:Gopibag,City:Dhaka,Landmark:f", "r_area":"Gulshan-2","r_type":"BOX", "r_time":"2017-01-20 12:00:09", "agent":"Sayeed","paymentmethod":"COD","paymentclear":"Clear", "r_timing":"Next Day(24hr)","r_coverage":"Inside Dhaka", "r_weight":"Up To 500gm","product_price":"10000", "shipping_price":"60","cod":100] } ** There could be multiple cEourier_ids if product_id is not unique</pre>
401 Unauthorized Access	<pre>User doesn't have permission or authentication failed due to wrong credentials { "errors": ["Unauthorized Access"], "response_code": 401 }</pre>
400 Bad Request	<pre>When Product ID or eCourier ID is invalid { "errors": ["Invalid Data", "Please Set product id or ecr number or both"], "response_code":400 }</pre>

2.3 Packages

- ✧ Purpose: To get assigned package list
- ✧ Method: POST
- ✧ Path: /packages

2.3.1 Request Format

Header	Body
Headers [API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json]	Body

2.3.2 Response Format

Status	Response
200	Available Package data will be found [{"package_name": "SAMEDAY_Inside_120tk", "package_code": "#2505", "shipping_charge": "120", "weight": "Up To 500gm", "delivery_time": "Same Day(8Hr)", "coverage_id": "1", "coverage": "Inside Dhaka" }, {...} }, { ... }]
401 Unauthorized Access	User does not have permission or authentication failed due to wrong credentials { "errors": ["Unauthorized Access"], "response_code": 401 }

2.4 Cancel Order

- ✧ Purpose: To cancel an order while parcel status is “Initiated API” or “Initiated”
- ✧ Method: POST
- ✧ Path: /cancel-order

2.4.1 Input Parameters

Name	TYPE	MOC	Description	Sample value
tracking	String	Mandatory	Your eCourier ID	ECR12312321
comment	String	Mandatory	Reason for cancel. But not more than 255 characters.	Customer does not like

2.4.2 Request Format

Header	Body
Headers [API-SECRET:YOUR_SECRET	Body {

<pre> API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json] </pre>	<pre> "tracking": "ECR103132312321", "comment": "cancel comment" } </pre>
--	---

2.4.3 Response Format

Status	Response
200	If tracking available with editable status and canceled <pre>{ "success": "true", "message": "Order canceled" }</pre> If tracking available with editable status but not canceled <pre>{ "success": "false", "message": " Order not canceled" }</pre> If tracking not available. <pre>{ "success": "false", "message": "Invalid Tracking" }</pre>
401 Unauthorized Access	User doesn't have permission or authentication failed due to wrong credentials <pre>{ "errors": ["Unauthorized Access"], "response_code": 401 }</pre>

2.5 Fraud Alert Check

- ✧ Purpose: To check any custom probability of fraudulent activity
- ✧ Method: POST
- ✧ Path: /fraud-status-check

2.5.1 Input Parameters

Name	TYPE	MOC	Description	Sample value
number	String	Mandatory	Customer mobile number	01XXXXXXXXXX

2.5.2 Request Format

Header	Body
Headers [<pre> API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json] </pre>	Body <pre> { "number": "01xxxxxxxxx" } </pre>

2.5.3 Response Format

Status	Response
200	<pre>{ "success": true, "response_code": 200, "customer_status": "Warning!", "message": [</pre>

	<pre> "Reason of fraud"] } { "success": true, "response_code": 200, "customer_status": "New Customer for eCourier", "message": "" } { "success": true, "response_code": 200, "customer_status": "Verified by eCourier", "message": "" } { "success": false, "response_code": 203, "message": "Invalid number. Please provide a valid number." } { "success": false, "response_code": 203, "message": "Please contact with eCourier support to enjoy this service" } { "success": false, "response_code": 203, "message": " Insufficient COD Balance" } </pre>
401 Unauthorized Access	<pre> User doesn't have permission or authentication failed due to wrong credentials { "errors": ["Unauthorized Access"], "response_code": 401 } </pre>

2.6 City List

- ❖ Purpose: To get City List
- ❖ Method: POST
- ❖ Path: /city-list

2.6.1 Request Format

Header	Body
Headers [API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY	Body

USER-ID:USER_ID Content-Type: application/json]	
--	--

2.6.2 Response Format

Status	Response
200	Listed Cities [{ "name": "Dhaka", "value": "Dhaka" }, {..... }, {..... }]
401 Unauthorized Access	User doesn't have permission or authentication failed due to wrong credentials { "errors": ["Unauthorized Access"], "response_code": 401 }

2.7 Thana List

- ✧ Purpose: To get Thana List
- ✧ Method: POST
- ✧ Path: /thana-list

2.7.1 Input Parameters

Name	TYPE	MOC	Description	Sample value
city	String	Mandatory	City Name	Barishal

2.7.2 Request Format

Header	Body
Headers [API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json]	Body

2.7.3 Response Format

Status	Response
200	<pre>["success": true, "message": [{ "name": "Agailjhara", "value": "Agailjhara" }, { "name": "Babuganj", "value": "Babuganj" }, {... }, { ... }]</pre>
401 Unauthorized Access	<pre>User doesn't have permission or authentication failed due to wrong credentials { "errors": ["Unauthorized Access"], "response_code": 401 }</pre>
400 Bad Request	<pre>Invalid Request { "errors": ["Invalid Request", " Thana not found by your search"], "response_code": 400 }</pre>
400 Bad Request	<pre>Invalid Request { "errors": ["Invalid Request", " Please select thana"], "response_code": 400 }</pre>

2.8 Area List by Post Code

- ✧ Purpose: To get Area List
- ✧ Method: POST
- ✧ Path: /area-list

2.8.1 Input Parameters

Name	TYPE	MOC	Description	Sample value
postcode	String	Mandatory	Post code	1212

2.8.2 Request Format

Header	Body
Headers [<pre> API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json </pre>]	Body <pre> "postcode": 1212 </pre>

2.8.3 Response Format

Status	Response
200	<pre> { "success": true, "message": [{ "name": "Abdullah Bag", "value": "Abdullah Bag" }, { "name": "Adorsho Nagor", "value": "Adorsho Nagor" }, { "name": "Agora", "value": "Agora" }] } </pre>
401 Unauthorized Access	User doesn't have permission or authentication failed due to wrong credentials <pre> { "errors": ["Unauthorized Access"], "response_code": 401 } </pre>
400 Bad Request	Invalid Data <pre> { "errors": ["Invalid Request", "Area not found by your search. "], "response_code": 400 } </pre>
400 Bad Request	Invalid Request <pre> { "errors": [</pre>

	<pre>"Invalid Data", " Please select postcode. "], "response_code": 400 }</pre>
--	--

2.9 Post Code List

- ✧ Purpose: To get Post Code List
- ✧ Method: POST
- ✧ Path: /postcode-list

2.9.1 Input Parameters

Name	TYPE	MOC	Description	Sample value
city	String	Mandatory	City Name	Barishal
thana	String	Mandatory	Thana Name	Babuganj

2.9.2 Request Format

Header	Body
<pre>Headers [API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json]</pre>	<pre>Body "city": "Barishal" "thana": "Babuganj"</pre>

2.9.3 Response Format

Status	Response
200	<pre>"success": true, "message": [{ "name": "8210(Babuganj)", "value": "8210" }, { "name": "8217(Babuganj Bondor)", "value": "8217" }, ]</pre>
401 Unauthorized Access	<pre>User doesn't have permission or authentication failed due to wrong credentials { "errors": ["Unauthorized Access"], "response_code": 401 }</pre>
400 Bad Request	<pre>Invalid Request { "errors": ["Invalid Data",</pre>

	<pre>"Postcode Not found by your search. "], "response_code": 400 }</pre>
400 Bad Request	<pre>Invalid Request { "errors": ["Invalid Data", "Please select city and thana. "], "response_code": 400 }</pre>

2.10 Branch List

- ✧ Purpose: To get Branch List
- ✧ Method: POST
- ✧ Path: /branch-list

2.10.1 Request Format

Header	Body
<pre>Headers [API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json]</pre>	Body

2.10.2 Response Format

Status	Response
200	<pre>"success": true, "message": [{ "name": "Andarkilla Hub", "value": 57 }, { }]</pre>
401 Unauthorized Access	<pre>User doesn't have permission or authentication failed due to wrong credentials { "errors": ["Unauthorized Access"], "response_code": 401 }</pre>

2.11 Booster SMS Service

- ✧ Purpose: To broadcast SMS using Booster SMS service

- ✧ Method: POST
- ✧ Path: /bs-sms

2.11.1 Input Parameters

Name	TYPE	MOC	Description	Sample value
number	Array	Mandatory	Mobile Number	["01XXXXXXXXXX"]
op_title	String	Mandatory	Service Name	booster
text_type	String	Mandatory	Type of the text	text
op_body	String	Mandatory	Operation Body	hello js
service_type	String	Mandatory	Masking or Non Masking	mask for masking nonmask for non masking

2.11.2 Request Format

Header	Body
Headers [API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json]	Body "number": ["01XXXXXXXXXX"] "op_title": "booster" "text_type": "text" "op_body": "hello js" "service_type": "mask"

2.11.3 Response Format

Status	Response
200	<pre>{ "success": true, "response_code": 200, "message": "All SMS sent", "wrong": [] }</pre>
206	<pre>{ "success": true, "response_code": 206, "message": "Few SMS not sent", "wrong": ["880183495469"] }</pre>
204	<pre>{ "success": false, "response_code": 204, "message": "SMS not sent.", "wrong": ["880173857162", "880183495469"] }</pre>
203	<pre>{ "success": false, "response_code": 203, "message": "Insufficient COD Balance" }</pre>
207	<pre>{ "success": false, "response_code": 207, "message": "Missing Mandatory data" }</pre>
406	<pre>{ "success": false, "response_code": 406, "message": "SMS rate not define. Contact eCourier support." }</pre>

404	{ "success": false, "response_code": 404, "message": "Your masking name missing. Contact eCourier Support" }
400 Bad Request	{ "errors": ["Invalid Request", null], "response_code": 400, "success": false }

2.12 Booster Service Top-up

- ✧ Purpose: To top-up Booster Service account
- ✧ Method: POST
- ✧ Path: /bs-top

2.12.1 Input Parameters

Name	TYPE	MOC	Description	Sample value
number	String	Mandatory	Mobile Number	01XXXXXXXXXX
amount	Integer	Mandatory	Top Up Amount	50
operator_type	Integer	Mandatory	Type of the operator	Value -> 1 for prepaid, Value -> 2 for postpaid Default value 1

2.12.2 Request Format

Header	Body
Headers [API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json]	Body "number": "01XXXXXXXXXX" "amount": "10" "operator_type": "1"

2.12.3 Response Format

Status	Response
200	{ "success": true, "response_code": 200, "transction_id": "2388_1548834510_74832", "message": "Request Successfully Accepted. Your transaction ID is 2388_1548834510_74832" }
400	{ "errors": ["Invalid Request", null], "response_code": 400, }

	<pre>"success": false }</pre>
401	<pre>{ "success": false, "response_code": 401, "message": "Invalid Mobile Number. Please try with the correct mobile number" }</pre>
402	<pre>{ "success": false, "response_code": 402, "message": "Insufficient COD Balance" }</pre>
403	<pre>{ "success": false, "response_code": 403, "message": "Unable to process now. Please try again later and contact eCourier support" }</pre>
404	<pre>{ "success": false, "response_code": 404, "message": "Missing required data" }</pre>
405	<pre>{ "success": false, "response_code": 405, "message": "Top up amount must be between 50 to 1,000 TK." }</pre>

2.13 Booster Top-up Status Check

- ✧ Purpose: To check Booster top-up service
- ✧ Method: POST
- ✧ Path: /bs-top-status

2.13.1 Input Parameters

Name	TYPE	MOC	Description	Sample value
transaction_id	String	Mandatory	Transaction Id	10_1590903041_38811

2.13.2 Request Format

Header	Body
Headers [<pre>API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json</pre>]	Body <pre>"transaction_id": "10_1590903041_38811"</pre>

2.13.3 Response Format

Status	Response
200	<pre>{ "success": true, "message": "Successfully recharged" }</pre>

400	<pre> } { "errors": ["Invalid Request", null], "response_code": 400, "success": false } </pre>
401	<pre> { "success": false, "response_code": 401, "message": "Invalid transaction ID supplied" } </pre>
403	<pre> { "success": false, "response_code": 403, "message": "Unable to process now. Please try again later and contact eCourier support " } </pre>
404	<pre> { "success": false, "response_code": 404, "message": "Missing required data" } </pre>

2.14 OTP SMS

- ❖ Purpose: To avail OTP SMS Service
- ❖ Method: POST
- ❖ Path: /bs-top-otp

2.14.1 Input Parameters

Name	TYPE	MOC	Description	Sample value
number	String	Mandatory	Mobile Number	01XXXXXXXXXX
op_title	String	Mandatory	Service Name	booster
text_type	String	Mandatory	Type of the text	text
op_body	String	Mandatory	Operation Body	hello js
service_type	String	Mandatory	Masking or Non Masking	mask

2.14.2 Request Format

Header	Body
Headers [<pre> API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json </pre>]	Body <pre> "number": "01XXXXXXXXXX" "op_title": "booster" "text_type": "text" "op_body": "hello js" "service_type": "mask" </pre>

2.14.3 Response Format

Status	Response
200	<pre> { "success": true, "response_code": 200, "message": "All SMS sent", "wrong": [] } </pre>

206	<pre>{ "success": true, "response_code": 206, "message": "Few SMS not sent", "wrong": ["880183495469"] }</pre>
204	<pre>{ "success": false, "response_code": 204, "message": "SMS not sent.", "wrong": ["880183495469"] }</pre>
203	<pre>{ "success": false, "response_code": 203, "message": "Insufficient COD Balance" }</pre>
207	<pre>{ "success": false, "response_code": 207, "message": "Missing required data" }</pre>
406	<pre>{ "success": false, "response_code": 406, "message": "SMS rate not define. Contact eCourier support." }</pre>
404	<pre>{ "success": false, "response_code": 404, "message": "Your masking name missing. Contact eCourier Support" }</pre>
400 Bad Request	<pre>{ "errors": ["Invalid Request", null], "response_code": 400, "success": false }</pre>

2.15 Child Parcel Tracking

- ✧ Purpose: To track child parcel
- ✧ Method: POST
- ✧ Path: /track-child

2.15.1 Input Parameters

Name	TYPE	MOC	Description	Sample value
Ecr	String	Conditional	Your eCourier ID	ECR1012312321312

2.15.2 Request Format

Header	Body
Headers [<pre> API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json </pre>]	Body <pre> { "product_id": "1234", "ecr": "ECR0032042424" } Or { "product_id": "1234" } Or { "ecr": "ECR0032042424" } </pre>

2.15.3 Response Format

Status	Response
200 Request accepted	When Order doesn't exist <pre> { "response_code": 200, "success": false, "query_data": "No Data Found" } </pre>
200 Request accepted	When Data Found <pre> { "response_code": 200, "success": true, "query_data": [{ "status": [["Delivered", "", "2017-01-20 12:04:55"], ["On the way to Delivery", "Status has been changed", "2017-01-20 12:03:39"], ["In Destination Branch", "Status has been changed", "2017-01-20 12:03:34"], ["In Transit", "Status has been changed", "2017-01-20 12:03:25"], ["In Source Branch", "Status has been changed", "2017-01-20 12:03:20"], ["Picked Up", "Status has been changed", "2017-01-20 12:01:37"], ["Initiated", "An order has been made by ecommerce", "2017-01-20 12:00:09"]], "REFID": "ECR1022001175478", "company": "MyTOTOcompany", "product_id": "", "r_name": "Mannan", "r_mobile": "01848308508", "r_address": "House:d,Block:d,Road:d,Area:Gopibag,City:Dhaka,Landmark:f", "r_area": "Gulshan-2", "r_type": "BOX", "r_time": "2017-01-20 12:00:09", "agent": "Sayeed", "paymentmethod": "COD", "paymentclear": "Clear", "r_timing": "Next Day(24hr)", "r_coverage": "Inside Dhaka", "r_weight": "Up To 500gm", "product_price": "10000", </pre>

	<pre> "shipping_price": "60", "cod": 100 }] } </pre> <p>** There could be multiple cCourier_ids if product_id is not unique</p>
401 Unauthorized Access	<p>User doesn't have permission or authentication failed due to wrong credentials</p> <pre> { "errors": ["Unauthorized Access"], "response_code": 401 } </pre>
400 Bad Request	<p>When Product ID or eCourier ID is invalid</p> <pre> { "response_code": 200, "success": false, "query_data": "Please set ECR number" } </pre>

2.16 Label Print

- ✧ Purpose: To track child parcel
- ✧ Method: POST
- ✧ Path: /label-print

2.16.1 Input Parameters

Name	TYPE	MOC	Description	Sample value
tracking	String	Conditional	Your eCourier ID	ECR1012312321312

2.16.2 Request Format

Header	Body
<pre> Headers [API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json] </pre>	<pre> Body { "tracking": "ECR1184902409200325" } </pre>

2.16.3 Response Format

Status	Response
200 Request accepted	<p>When Order doesn't exist</p> <pre> { "success": false, "response_code": 200, "query_data": "Parcel not found" } </pre>

200 Request accepted	When Data Found <pre>{ "success": true, "response_code": 200, "query_data": "https://staging.ecourier.com.bd/invoices/print_slip1604833594_2160.pdf" }</pre>
401 Unauthorized Access	User doesn't have permission or authentication failed due to wrong credentials <pre>{ "errors": ["Unauthorized Access"], "response_code": 401 }</pre>
400 Bad Request	When tracking is missing <pre>{ "success": false, "response_code": 200, "query_data": "Tracking ID required" }</pre>

2.17 Child Parcel Cancel

- ✧ Purpose: To cancel an order while parcel status is “Initiated API” or “Initiated”
- ✧ Method: POST
- ✧ Path: /cancel-order-child

2.17.1 Input Parameters

Name	TYPE	MOC	Description	Sample value
tracking	String	Mandatory	Your eCourier ID	ECR12312321
comment	String	Mandatory	Reason for cancel. But not more than 255 characters.	Customer does not like

2.17.2 Request Format

Header	Body
Headers [<pre>API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json</pre>]	Body <pre>{ "tracking": "ECR103132312321", "comment": "cancel comment" }</pre>

2.17.3 Response Format

Status	Response
200	If tracking available with editable status and canceled <pre>{ "success": "true", "message": "Order canceled" }</pre> If tracking available with editable status but not canceled <pre>{ "success": "false", "message": " Order not canceled" }</pre> If tracking not available. <pre>{ "success": "false", "message": "Invalid Tracking" }</pre>

401 Unauthorized Access	User doesn't have permission or authentication failed due to wrong credentials <pre>{ "errors": ["Unauthorized Access"], "response_code": 401 }</pre>
-------------------------------	--

2.18 Payment Status

- ✧ Purpose: To know about payment status by giving tracking
- ✧ Method: POST
- ✧ Path: /payment-status

2.18.1 Input Parameters

Name	TYPE	MOC	Description	Sample value
tracking	String	Mandatory	Your eCourier ID	ECR12312321

2.18.2 Request Format

Header	Body
Headers [<pre>API-SECRET:YOUR_SECRET API-KEY:YOUR_KEY USER-ID:USER_ID Content-Type: application/json</pre>]	Body <pre>{ "tracking": "ECR103132312321" }</pre>

2.18.3 Response Format

Status	Response
200	If any parcel has with status <pre>{ "success": true, "message": { "payment_id": 20, "payment_mode": "dbbl", "collected_amount": 500, "payment_date": "2020-12-07 18:05:18", "shipping_charge": 130, "booking_price": 8, "fragile_price": 0, "cash_on_delivery": 148 } }</pre> If invalid tracking <pre>{ "success": false, "message": "Order not Found" }</pre>
401 Unauthorized Access	User doesn't have permission or authentication failed due to wrong credentials <pre>{ "errors": ["Unauthorized Access"], "response_code": 401 }</pre>

	}
--	---

3.0 Response Code Definition

All status codes are standard HTTP status codes. The below ones are used in this API.

- ✧ 2XX - Success of some kind
- ✧ 4XX - Error occurred in client's part
- ✧ 5XX - Error occurred in server's part

4.0 Sandbox Base URL

<https://staging.ecourier.com.bd/api>

5.0 Live Base URL

<https://backoffice.ecourier.com.bd/api>